

# Smappee EV Ultra 240D



The Smappee EV Ultra is a floor-mounted fast charger with CCS2 connectors. The charging status and instructions are displayed on the integrated screen. This charger features a robust, compact, all-weather enclosure made from high-quality, recyclable materials. It also includes LED lighting for enhanced visibility and security.

Unlock Smappee's energy intelligence and charging management features with our business subscription plan\*:

- Maximize renewable energy consumption and improve overall energy efficiency.
- Reduce costs and minimize grid investment with dynamic load management.
- Monitor multiple chargers remotely and set up priority charging.
- Make chargers public with our CPO add-on, manage rates, and integrate Smappee Pay Station.
- Get over-the-air updates to always have the latest features and improvements and to cope with the cars' firmware changes

*\*The Business subscription plan is priced per connector and per month. Additional add-ons are available based on your needs.*

## Dimensions

- Charging station: 1870 × 920 × 325 mm
- Charging cables: 2 × 3,25 m

## Weight

- Charging station with cables: 340 kg
- Anchor: 22,5 kg

## Operating temperature

-25 °C to 50 °C (derating from 40 °C)

## Storage temperature

-25 °C to 70 °C

## Relative humidity

0 % - 95 %, non-condensing

## Operating altitude

0 - 2.000 m

## Standards

IEC 61851-21, ISO 15118, DIN SPEC 70121

## Product certification

CE, optional Eichrecht certified

## Connectivity

- Ethernet 100BASE-T (with fallback to 4G in case of connection loss)
- 4G Modem

## Communication protocol

OCPP 1.6 J, ready for update to OCPP 2.0.1

## Interfaces

- Information status: 2 × 6,5" RGB Display
- Session activation: QR code / RFID (Optional Smappee Pay Station)

## Mounting method

Floor, with supplied anchor

## Enclosure

- Material: powder coated steel
- Standard colour: RAL7021 (black grey) optional customization
- Rating: IP 54 / IK 10
- Acoustic noise: 0 dB - 60 dB
- Indoor / outdoor use

## Nominal input

- Main power: 3 × 400 V + PE / 350 A
- Auxiliary power: 3 × 400 V + N / 10 A
- Rated frequency (fn): 50 Hz
- Power factor: > 98 % at full capacity
- Efficiency: > 95 % at full capacity

## DC Output

- Nominal power charging point: Maximum 120 kW
- Nominal power charging station: Maximum 240 kW
- Charge mode: Mode 4 (IEC 61851)
- DC Plug: CCS2